



**Fig. 1**

**Fig. 2**

**DATI TECNICI, TECHNICAL DATA**

Temperatura <b>TS</b> - C Temperature <b>TS</b> - C	Min. <b>-10</b> Max. <b>+120</b>	Min. <b>-50</b> Max. <b>+120</b>	Pressione di collaudo <b>PT</b> Test pressure <b>PT</b>
Pressione max. consentita <b>PS</b> -bar Max permissible pressure <b>PS</b> -bar	<b>45</b>	<b>33</b>	<b>PT-bar: 64.35 (45x1.43)</b>

Refrigeranti/Refrigerants: R22,R502,R134a,R401A,R401B,R402A,R402B,R404A,R407C,R410A,R507 e altri/ and other ones

PED CAT.	TIPO / TYPE	VOLUME litri litres	FIG.	DIMENSIONI DIMENSIONS				ATTACCHI CONNECTIONS		SUPERFICIE FILTRANTE STRAINING AREA (cmq)	SUPERFICIE UTILE PASSAGGIO USEFUL PASSING AREA (cmq)	LUCE MAGLIA MESH GAP (mm)
				A	B	C	D	IN	OUT			
Art. 3§3	FO-65x113-ODS 3/8"	0.32	FIG. 1	65	69	159	113	ODS 3/8"		90	22.5	0.15 ÷ 0.18
	FO-65x113-ODS 10	0.32		65	69	159	113	ODS 10				
	FO-65x113-ODS 12	0.32		65	69	159	113	ODS 12				
	FO-65x113-ODS 1/2"	0.32		65	69	159	113	ODS 1/2"				
	FO-65x113-1/4"SAE	0.32	FIG. 2	65	69	159	113	1/4"SAE				
	FO-65x113-3/8"SAE	0.32		65	69	163	113	3/8"SAE				
	FO-65x113-1/2"SAE	0.32		65	69	163	113	1/2"SAE				